



JUN 28
4651 10515
82 13:32

FLEX PREMIUM NEAR-EDGE WAX-RESIN RIBBON

TTR PROPERTIES	
Base Film Thickness	4.0 ± 1.0µ
Total Thickness	6.5 ± 1.0µ
Ink Color	Black
Ink Melting Point	70~80°C
Max Print Speed	700mm/second* *substrate & application dependent

RESISTANCE	
Scratch	Very Good
Smear	Very Good
Solvent	Fair
Water	Excellent

RECOMMENDED SUBSTRATES	
Papers	Coated
Synthetics	PP, PET, Tyvek
Films	Flexible Packaging

Storage: 5° to 35°C; 30 to 85% RH; Shelf Life 1 Year

CERTIFICATIONS

- » FDA Listed
- » Deemed Food Safe (LGFB, FDA 21, CFR 175.300)
- » RoHS (2002/95/EC)

RECOMMENDED APPLICATIONS

- FLEXIBLE PACKAGING
- MEDICAL & HEALTHCARE
- FOOD & BEVERAGE
- CONFECTIONS
- RETAIL & HANGTAGS
- INVENTORY & LOGISTICS
- HIGH-SPEED PRINTING
- DATE, LOT & BARCODE PRINTING
- POLY-BAG APPLICATIONS
- COMPLIANCE LABELING

SAMPLES AVAILABLE TO TEST IN YOUR APPLICATION