



FEB 26 2018
070104823R
PRODUCT OF
USA
B6LN261C

FLEX ULTRA NEAR-EDGE WAX-RESIN RIBBON

TTR PROPERTIES	
Base Film Thickness	4.0 ± 0.5µ
Total Thickness	6.0 ± 1.0µ
Ink Color	Black
Ink Melting Point	80°C
Max Print Speed	500mm/second* *substrate & application dependent

RESISTANCE	
Scratch	Excellent
Smear	Excellent
Solvent	Good
Water	Excellent

RECOMMENDED SUBSTRATES	
Papers	Coated, Uncoated
Synthetics	PP, PET, Tyvek
Films	Flexible Packaging

Storage: 5° to 35°C; 30 to 85% RH; Shelf Life 1 Year

CERTIFICATIONS

- » FDA Listed
- » Deemed Food Safe (LFGB, 1935/2004/EC)
- » Japanese Food Sanitation Law

RECOMMENDED APPLICATIONS

- FLEXIBLE PACKAGING
- INVENTORY & LOGISTICS
- COMPLIANCE LABELING
- HIGH-SPEED PRINTING
- FOOD & BEVERAGE
- DATE, LOT & BARCODE PRINTING
- CONFECTIONS
- POLY-BAG APPLICATIONS
- RETAIL & HANGTAGS

AVAILABLE COLORS: **BLACK, WHITE, & SILVER**

SAMPLES AVAILABLE TO TEST IN YOUR APPLICATION